

## Master control and web interface with SmartScan wireless communication

Transmits SmartScan and SmartScan emergency luminaire status reports to the SmartScan web server. Monitors and controls up to 50 wireless luminaires - ideal for smaller projects. Controls emergency lighting testing dates/times and external lighting switching times.

- Polycarbonate body finished white (RAL9016)
- Central monitoring for up to 50 SmartScan and SmartScan emergency luminaires - ideal for smaller projects
- Central time control for SmartScan External luminaires
- Communicates with the SmartScan website using MQTT mobile telecommunications
- Enables scheduled emergency test times / dates managed using the SmartScan website
- Status Indicators show operational condition
- Software security updates will be provided for a minimum of 10 years
- Ethernet connection for alternate connectivity to SmartScan website



Notes: SmartScan Gateway Lite is limited to a single poll every 24 hours and no live occupancy detection option.



---

## Specification


IP rating **IP65**

---

## Compliance

UKCA	Yes	CE	Yes
------	-----	----	-----

## Dimensions





**Click or scan here**  
View SmartScan Gateway Lite  
variants using our online  
filtering tool



Information is correct as of 29-Dec-2024, however must not be interpreted as a guarantee of individual product performance and/or characteristics. We reserve the right to alter specifications and designs without prior notice.